

Quotation of HBT40 trailer Concrete Pump**Payment terms**

1.30% by T/T as advance payment with 7days after the contract signed, the balance of 70% by irrevocable L/C at sight.

Delivery Schedule

Delivery should be within 20 days from the date of receipt of 40% down payment.

Warrantee

The warranty will be one year from the date of shipment. Any detected parts during this period caused by the quality of products will be replaced by seller free of cost (exclude wear and tear parts), improper operation and other manmade reasons are excluded.



Shandong Rhinoceros Engineering Machinery CO., LTD

Technical parameters:

Model No./Concrete pump	HBT40
Max. theoretical concrete output(m ³ /h)	Low pressure 48 /high pressure 23
Max. theoretical concrete pumping pressure(Mpa)	Low pressure 5.3 /high pressure 11
Theoretical vertical conveying height(m)	150
Theoretical level transmission distance(m)	400
Allowing the concrete slump(mm)	100-230
Max. Aggregate particles(mm)	40/35
Hopper volume(m ³)	0.5
Filling height(mm)	1100
Concrete cylinder diameter × stroke(mm)	Φ180×1800
Main oil cylinder diameter(mm)	Φ100
Max stroke(mm)	1800
Dynamic brand	Diesel engine
Dynamic model	R4105ZD2
Rated power(kw)	66
Fuel consumption(g/h.kw)	227
Hydraulic system	Double circuit opening system
Brand of main pump	Kawasaki
Discharge of main pump(ml)	112
Max. hydraulic system pressure(Mpa)	25
Hydraulic oil tank volume(L)	320
The radiator cooling	Air cooling system
Electric control	PLC
Concrete tube conveying diameter(mm)	Φ108/Φ133
Max. towing speed(km/h)	15
Overall dimension(L×W×H)(mm)	4850×1670×2070
Total weight(kg)	3360
Hydraulic pump type	Ram pump