



Shandong Rhinoceros Engineering Machinery CO., LTD

HBT30C ELECTRIC CONCRETE PUMP SPECIFICATION:

Item	Unit	HBT30C
(Electric Concrete pump)		
Max. Theoretical Concrete Output	m ³ /h	30
Max. Concrete Pumping Pressure	Mpa	10
Distribution valve		S Valve
Conveying tube inner Dim	mm	Φ100A/80A
Concrete Cylinder Diameter	mm	Φ160×1000
Hopper Capacity/ Filling Height	m ³ /mm	0.4/1100
Maximum aggregate size	mm	30
Concrete slump range	mm	120-230
Power	kw	45
Rated speed	r/min	1480
Voltage/frequency	V/Hz	380/50
Max. Theoretical Conveying Distance (Horizontal/Vertical)	m	400/150
Hydraulic Fuel tank capacity	L	200
Cleaning mode		High pressure washing
Dimension	mm	4500*1500*1800
Total Weight (including oil)	kg	3000

Attachment-1: List of Tools and Wear Parts		
Item	Specification	Quantity
Grease gun		1
Rubber sponge ball		2
Lithium base grease	00#	2
Spud		1
Slotted screwdriver		1
Cross screwdriver		1
Allen key	3-14	1
Double-ended spanner	6-32	1
Double-ended spanner	34-36	1
Double-ended spanner	36-41	1
Hand mallet		1
Hand vice		1
Jack		1
Spanner		1
Spanner special for back-end of S tube		1
Sealing		1
Rubber spring		1

ADD: Dingyuanzhai Industrial Park, 18km east of liaocheng, Shandong Province, China.

Tel: 0086-635-5663999 Fax: 0086-635-5846000

Shandong Rhinoceros Engineering Machinery CO., LTD

Square ring		2
Chipping chisel		1
Spear point chisel		1
Piston		1
Cable	3×16+2	40
Remote control		1
Work light		1
Cylinder seal		2

Attachment-2: Delivery Pipe		
Name	Type	Quantity
straight pipe	Φ125*3M	13
straight pipe	Φ125*2M	2
straight pipe	Φ125*1M	3
hose	Φ125*3M	1
curving pipe	Φ125A90°R500	4
curving pipe	Φ125A45°R500	2
curving pipe	Φ125A30°R500	2
rubber ring	Φ125	60
pipe clamp	Φ125	27

MACHINE PHOTOS

