



Shandong Rhinoceros Engineering Machinery CO., LTD

WHEEL LOADER ZL30 SPECIFICATION:

Performance	Rated Load	2800 kg
	Total weight	7000 kg
	Rated Bucket Capacity	1.5 m ³
	Max.Gradeability	30°
	Dumping Height	3500mm
	Overall Dimemsions(LxWxH)	6400x2180x2900mm
	Min.Turning Radius	4800mm
Engine	Model	YTO(YTR4108)
	Type	In-line,Water-cooled,Four-stroke,Direct injection, four- cylinder
	Rated Power	74.9kw
	Rated Speed	2400 rpm
Transmission	Gear box	Counter shaft power shift
	Torque converter	XN280
	Gear Shift	2 forward, 2 reverse
	Max.Speed	30 km/h
Drive Axle	Model of Axle	Hub Reduction Axle
	Wheel Base	2400 mm
Hydraulic System	System Working Pressure	16 Mpa
	Raising Time	≤ 5.5 s
	Total Cycle Time	≤ 10.0 s
	function of leveling automatically	Yes
Brake system	Service Brake	Hydraulic,Expansion-shoe Brake on 4 wheels
	Parking Brake	manual Flexible Shaft Control Disc Brake
Tyre	Type Specification	16/70-24
	Front Tyre Pressure	0.3 Mpa
	Rear Tyre Pressure	0.28 Mpa

WHEEL LOADER ZL30 PHOTOS

ADD: Dingyuanzhai Industrial Park, 18km east of liaocheng, Shandong Province, China.

Tel: 0086-635-5663999 Fax: 0086-635-5846000

