



# Shandong Rhinoceros Engineering Machinery CO., LTD

## XNF30 HYDRAULIC FORKLIFT

### MAIN SPECIFICATION

Load capacity kg	3000
Load center mm	500
Power type	DIESEL
Max.lifting speeds(with load) mm/s	400
Max.driving speeds(with/without load) km/h	18/20
Max.towing(with/without load) kN	15.5/10.5
Gradeability(with/without load) %	15/20
Lifting height mm	3000
Free lift mm	80
Tilting angles(forward-backward)	6/12
Min.turning radius mm	2500
Min.right angle aisle width mm	2110
Min.under-clearance mm	135
Overall length(include fork) mm	3800
Overall width mm	1230
Overall height(mast lowered) mm	2110
Overall height(mast extended) mm	4270
Overall height to overhead guard mm	2110
Fork overhang mm	465
Wheel base mm	1750
Front tread mm	1000
Rear tread mm	970
Front tyre	28x9-15
Rear tyre	6.50-10
Total weight kg	4320
Fork width mm	125
Fork thickness mm	45
Backrest height mm	1225
Fork length mm	1220
Engine model	490
Rate power kw	39
Rotate speed at rate power rpm	2650
Max.torque Nm	157
Rotate speed at max torque rpm	1980
Emission standard	CHINA II
Type of power shift	Hydraulic

FORKLIFT PHOTOS

