



Shandong Rhinoceros Engineering Machinery CO., LTD

XNF50 5.0T HYDRAULIC FORKLIFT

MAIN SPECIFICATION

Load capacity kg	5000
Load center mm	600
Power type	DIESEL
Max.lifting speeds(with load) mm/s	470
Max.driving speeds(with/without load) km/h	21/23
Max.towing(with/without load) kN	52
Grade ability(with/without load) %	20/25
Lifting height mm	6000
Free lift mm	150
Tilting angles(forward-backward)	6/12
Min.turning radius mm	3430
Min.right angle aisle width mm	3090
Min.under-clearance mm	230
Overall length(include fork) mm	4760
Overall width mm	1995
Overall height(mast lowered) mm	2500
Overall height(mast extended) mm	4420
Overall height to overhead guard mm	2420
Fork overhang mm	630
Wheel base mm	2250
Front tread mm	1470
Rear tread mm	1700
Front tyre	8.25-15-14
Rear tyre	8.25-15-14
Total weight kg	8200
Fork width mm	150
Fork thickness mm	55
Backrest height mm	1365
Fork length mm	1220
Engine model	ISUZU(6BG1-02)
Rate power kw	82
Max.torque Nm	353/400
Rotate speed at max torque rpm	1650/1600-1800
Emission standard	CHINA II
Battery	2-12V/80AH
Type of power shift	Hydraulic

FORKLIFT PHOTOS

