



Shandong Rhinoceros Engineering Machinery CO., LTD

XNF100 5.0T HYDRAULIC FORKLIFT

MAIN SPECIFICATION

Load capacity kg	10000
Load center mm	600
Power type	DIESLE
Max.lifting speeds(with load) mm/s	310
Max.driving speeds(with/without load) km/h	16/22
Max.towing(with/without load) kN	58
Grade ability(with/without load) %	19/20
Lifting height mm	3000
Free lift mm	150
Tilting angles(forward-backward)	6/12
Min.turning radius mm	4000
Min.right angle aisle width mm	3540
Min.under-clearance mm	250
Overall length(include fork) mm	5500
Overall width mm	2275
Overall height(mast lowered) mm	2850
Overall height(mast extended) mm	4300
Overall height to overhead guard mm	2585
Fork overhang mm	720
Wheel base mm	2800
Front tread mm	1600
Rear tread mm	1700
Front tyre	9.00-20-14
Rear tyre	9.00-20-14
Total weight kg	12510
Fork width mm	175
Fork thickness mm	80
Backrest height mm	1015
Fork length mm	1220
Engine model	CHAOCHAI 6102-BG
Rate power kw	80.9
Max.torque Nm	353
Rotate speed at max torque rpm	1650
Emission standard	CHINA II
Battery	2-12V/80AH
Type of power shift	Hydraulic

FORKLIFT PHOTOS



Shandong Rhinoceros Engineering Machinery CO., LTD

